UNIVERSITÀ
DEGLI STUDI
FIRENZE

**DIPARTIMENTO
DI FISICA E
ASTRONOMIA**

Light on Optics and Optometry

Tomografia Scheimpflug

12 Aprile 2024 – Lorenzo Fini

- le origini del metodo
- l'applicazione alla tomografia del segmento anteriore dell'occhio
- confronto tra le varie strumentazioni disponibili

Theodor Scheimpflug (1865-1911)

brevetto del 1904: Improved Method and Apparatus for the Systematic Alteration or Distortion of Plane Pictures and Images by Means of Lenses and Mirrors for Photography and for other purposes

disegno originale dal brevetto del 1904
(H. M. Merklinger, Scheimpflug's patent. Photo
Techniques, Nov/Dec 1996)

Jules Carpentier (1851-1921)

Jules Carpentier (1851-1921)

illustrazioni dal brevetto Inglese (GB 1139/1901)
(H. M. Merklinger, Scheimpflug's patent. Photo Techniques,
Nov/Dec 1996)

la regola di Scheimpflug

$$\frac{1}{z'} = \frac{1}{z} + \frac{1}{f'}$$
$$y' = \frac{z'}{z} y$$

la regola di Scheimpflug

$$\tan \theta' = \frac{z'_B}{z_B} \tan \theta$$

Fotografia Scheimpflug

Fotografia Scheimpflug

(fonte: wikipedia)

Fotografia Scheimpflug

(fonte: wikipedia)

La lampada a fessura

(www.csoitalia.it)

La lampada a fessura

Fini, test
P1143513220
Data di nascita: 01/01/1960

OD

180° → 0°

Orbscan II

La scansione ruotante

scansione ruotante

La scansione ruotante offre alcuni vantaggi rispetto alla scansione lineare:

- consente una rappresentazione più accurata della superficie posteriore della cornea
- le immagini acquisite hanno un punto in comune (il centro di rotazione) e questo rende più accurata la ricostruzione del modello tridimensionale del segmento anteriore
- maggiore densità di punti misurati vicino all'asse

Sirius+ di CSO

topografo a disco di Placido e
tomografo Scheimpflug

confronto tra alcuni tra gli strumenti più diffusi

modello	produttore	disco di Placido	Scheimpflug	illuminazione	n. immagini	
Orbscan II/IIz	Bausch & Lomb (USA)	✓		flash a luce bianca	40 (20 da destra e 20 da sinistra)	scansione parallela
Pentacam	Oculus (DE)		✓	LED 475 nm	da 25 a 100	
Sirius+	CSO (IT)	✓	✓	LED 475 nm	da 20 a 100	
Galilei	Ziemer Ophthalmology Co.(CH)	✓	✓	LED 470 nm	da 15 a 60	doppia telecamera

Fini, test
P1143513220
Data di nascita: 01/01/1960

OD

180° → 0°

Fini, test
P1143513220
Data di nascita: 01/01/1960

OD

Tast. freccia = sposta lente
Rotella mouse = zoom
Rotella mouse + Shift = cambia area

180° → 0°

Fini, test
P1143513220
Data di nascita: 01/01/1960

OD

180° → 0°

immagine del disco di Placido

analisi aberrometrica

quali informazioni si possono ottenere (Sirius+)

- mappa altimetrica della superficie anteriore/posteriore della cornea
- mappa di curvatura della superficie anteriore/posteriore
- mappa pachimetrica
- profondità della camera anteriore
- misura degli angoli irido-corneali
- analisi del fronte d'onda corneale e della qualità della visione
- mappa del potere frontale anteriore, potere frontale posteriore e potere equivalente dell'intera cornea.

campi di applicazione (Sirius+)

- Pianificazione della chirurgia per la correzione dei difetti refrattivi
- Screening del glaucoma
- Screening del cheratocono
- overview completa delle aberrazioni corneali. La mappa di OPD/WFE e le simulazioni visive (PSF, MTF, convoluzione di immagine) possono aiutare nella comprensione del disagio visivo del paziente;
- Modulo di calcolo della IOL (opzionale)
- Modulo per applicazione delle lenti a contatto

fonti di errore

- movimenti dell'occhio durante la misura
- distorsione geometrica (effetto della prospettiva)
- distorsione ottica dovuta all'osservazione attraverso la cornea
- anomalie e instabilità del film lacrimale
- stima dei parametri ottici (es. indice di rifrazione)
- saturazione del segnale nelle zone di maggiore backscattering (limbus)
- risoluzione delle immagini peggiore che negli OCT

analisi densitometrica

Figure 12. Multilinear densitometry showing the development of a spoke cataract in the lens of a 65-year-old patient.

(da: Clinical and Experimental Ophthalmology 2009; 37: 144–154 doi: 10.1111/j.1442-9071.2009.02018.x)

E' uno strumento versatile

Figure 10. Scheimpflug images and corresponding densitograms of young experimental animals. Every species has its typical lens light scattering profile.

(Clinical and Experimental Ophthalmology 2009; 37: 144–154 doi: 10.1111/j.1442-9071.2009.02018.x)

altre applicazioni delle immagini Scheimpflug

Immagine catturata da un dispositivo Scheimpflug della deformazione della cornea dovuta al getto del soffio d'aria prodotto dal tonometro Corvis ST (Oculus, Germany)

Sirius vs. OCT

Pachymetric measurements with a new Scheimpflug photography-based system

Intraobserver repeatability and agreement with optical coherence tomography pachymetry

Myriam Milla, MSc, David P. Piñero, PhD, Francisco Amparo, MD, Jorge L. Alió, MD, PhD

PURPOSE: To evaluate the intraobserver repeatability of pachymetric measurements obtained with a new Scheimpflug photography-based system and the agreement of the measurements with those obtained by optical coherence tomography (OCT).

SETTING: Visum Corporation, Alicante, Spain.

DESIGN: Evaluation of diagnostic technology.

METHODS: Corneal thickness was measured at different locations (center; 2.5 mm and 4.0 mm nasal, temporal, superior, and inferior) in 18 eyes of 18 patients with no ocular pathology or previous surgery with a Scheimpflug photography-based system (Sirius). Three consecutive measurements at each location were obtained with the system to evaluate intraobserver repeatability. Afterward, pachymetric measurements were obtained at the same locations with an OCT system (Visante) to evaluate the agreement between techniques using the Bland-Altman method.

RESULTS: The intraclass correlation coefficient of repeated measures ranged from 0.990 to 0.997. The coefficient of variation was lower than 1% and the standard deviations of the repeated measurements (S_w) were below 6 μm at all corneal locations. Statistically significant differences were found between the coefficient of variation and S_w values of the repeated measurements corresponding to the 2.5 mm and 4.0 mm locations ($P \leq .037$). The agreement with OCT pachymetric measurements was poor, with ranges of agreement larger than 20 μm at all corneal locations. Statistically significant differences were found between standard deviations of the differences between the 2 devices at the 2.5 mm and 4.0 mm locations ($P \leq .017$).

CONCLUSION: Scheimpflug photography-based technology provided repeatable pachymetric measurements that were not equivalent to those obtained with OCT.

Financial Disclosure: No author has a financial or proprietary interest in any material or method mentioned.

J Cataract Refract Surg 2011; 37:310–316 © 2011 ASCRS and ESCRS

The agreement with OCT pachymetric measurements was poor, with ranges of agreement larger than 20 μm at all corneal locations...

CONCLUSION: Scheimpflug photography-based technology provided repeatable pachymetric measurements that were not equivalent to those obtained with OCT.

Repeatability and Agreement of Horizontal Corneal Diameter Measurements Between Scanning-Slit Topography, Dual Rotating Scheimpflug Camera With Placido Disc Tomography, Placido Disc Topography, and Optical Coherence Tomography

Soobin Namkung, MBChB, Alexander Buckenham Boyle, MBChB, Ye Li, MBChB, Akilesh Gokul, Boptom (Hons), PhD, Charles McGhee, DSc, FRCOphth, and Mohammed Ziaei, MD, FRCOphth

Purpose: The purpose of this study was to assess the repeatability and agreement of horizontal white-to-white (WTW) measurements using 4 different imaging modalities including a slit-scanning elevation topographer, dual rotating Scheimpflug camera and Placido Disc tomographer, Placido Disc topographer, and anterior segment optical coherence (OCT) tomographer.

Methods: In this prospective study, 33 eyes of 33 healthy subjects

Conclusions: In healthy subjects the 4 devices demonstrated high repeatability in WTW measurement. However, a poor agreement between the devices suggests that they should not be used interchangeably for WTW measurements in clinical practice.

Key Words: horizontal corneal diameter, white-to-white, Orbscan II, Sirius, Nidek, optical coherence tomography

(*Cornea* 2022;41:1392–1397)

Pentacam vs. pachimetria a ultrasuoni

ORIGINAL ARTICLE

Comparison of Central Corneal Thickness Measurements by Contact and Non-contact Pachymetry Devices

Huseyin Mayali¹, Muhammed Altinisik², Ismail Diri³, Sami Ilker⁴, Emin Kurt⁵, Ozcan Kayikcioglu⁶

ABSTRACT

Aim and objective: To compare central corneal thickness (CCT) measurements obtained by handheld contact ultrasound pachymetry (HCUP) and non-contact pachymetry devices.

Materials and methods: Ninety eyes of 90 patients (52 male and 38 female) were included in the study. Measurements from two non-contact devices, —specular microscopy (SM, Konan Medical, CA, USA) and Oculus Pentacam (Oculus Inc., Germany)—were compared against HCUP (Pachmate 2, DGH Technology, Inc, PA, USA). Ultrasound measurements were obtained 3 times by the same user and averaged. The differences were calculated by one-way ANOVA. Agreement between measurements were assessed by Bland–Altman plots and intraclass correlation coefficient tests. Coefficient of repeatability (%), (CR) was defined as $1.96 \times$ standard deviations of the differences between pairs of measurements divided by the average of the means.

Results: The mean age was 34.31 ± 14.39 (14–74) years, and the mean intraocular pressure was 16.48 ± 2.63 mm Hg (12–21). Mean CCT measured by HCUP, SM, and Pentacam was 557.76 ± 36.76 μ m, 550.29 ± 43.74 μ m, and 541.41 ± 35.7 μ m, respectively ($p < 0.05$). In the Bland–Altman plot, 95% limit of agreements were 19.5 and 14.18 μ m among HCUP measurements, 34.55 μ m between HCUP and Pentacam, 41.49 μ m between SM and Pentacam, and 46.98 μ m between HCUP and SM. CR values (%) were 3.49, 2.54, 6.28, 7.68, and 8.47, respectively.

Conclusion: There were significant differences between the mean CCT values of the measurement devices.

Clinical significance: Contact and non-contact devices may not interchangeable in the clinical assessment of CCT.

Keywords: Central corneal thickness, Ocular tonometry, Pachmate, Pentacam, Specular microscopy.

Journal of Current Glaucoma Practice (2021): 10.5005/jp-journals-10078-1295

Scheimpflug vs Scanning-Slit Corneal Tomography: Comparison of Corneal and Anterior Chamber Tomography Indices for Repeatability and Agreement in Healthy Eyes

Pentacam HR vs. Orbscan II

This article was published in the following Dove Press journal:

[Clinical Ophthalmology](#)

Anastasios John Kanellopoulos^{1,2}

¹Department of Ophthalmology, The Laser-Vision Clinical and Research Eye Institute, Athens, Attiki, Greece;

²Department of Ophthalmology, New York University Medical School, New York City, NY, USA

Purpose: To evaluate and compare the repeatability and agreement of Scheimpflug vs scanning-slit tomography of the cornea and the anterior chamber in terms of keratometric and tomographic indices in healthy eyes.

Methods: The 20 eyes of 10 healthy participants underwent 3 consecutive measurements using both Scheimpflug-tomography and scanning-slit tomography, diagnostic devices. Multiple corneal and anterior chamber tomographic parameters were recorded and evaluated to include corneal keratometry and its axis; corneal best-fit sphere (BFS), pachymetry mapping, angle kappa, anterior chamber depth (ACD), pupil diameter, and location. Repeatability for each device was assessed using the within each subject standard deviation of sequential exams, the coefficient variation (CV) and the intraclass correlation coefficient (ICC).

Results: Both devices showed high repeatability and agreement. Scheimpflug tomography showed superior corneal pachymetry and anterior chamber depth measurements compared to scanning-slit tomography.

Conclusion: Scanning-slit tomography in this specific study, in most parameters evaluated, inter-device agreement evaluation suggests that reading from the two devices may not be used interchangeably in absolute values, yet they are well correlated with Scheimpflug delivering consistently lower values in most.

Keywords: Pentacam, Orbscan, Scheimpflug corneal tomography, scanning-slit corneal tomography

→ Video abstract

Point your Smartphone at the code above. If you have a QR code reader the video abstract will appear. Or use <http://www.lww.com/doi/10.1097/ICO.0000000000000000>

scanning-slit tomography in this specific study, in most parameters evaluated. Inter-device agreement evaluation suggests that reading from the two devices may not be used interchangeably in absolute values, yet they are well correlated with Scheimpflug delivering consistently lower values in most.

UNIVERSITÀ
DEGLI STUDI
FIRENZE

DIPARTIMENTO
DI FISICA E
ASTRONOMIA

Light on Optics and Optometry

Tomografia Scheimpflug

12 Aprile 2024 – Lorenzo Fini

grazie per l'attenzione!